

iiyama ProLite T2438MSC-B1 computerskærm 60,5 cm (23.8") 1920 x 1080 pixel Fuld HD LED Berøringsskærm Sort

Mærke : iiyama

Produktserie: ProLite

Produktkode: T2438MSC-B1

Produktnavn : T2438MSC-B1

iiyama ProLite T2438MSC-B1. Skærm diagonal: 60,5 cm (23.8"), Skærmopløsning: 1920 x 1080 pixel, HD-type: Fuld HD, Skærmteknologi: LED, Responstid: 5 ms, Naturligt aspektforhold: 16:9, Synsvinkel, horisontal: 178°, Synsvinkel, vertikal: 178°. Indbyggede højttaler(e). Indbygget USB-hub, USB-hub-version: 3.2 Gen 1 (3.1 Gen 1). VESA montering. Produktfarve: Sort



Display		Ergonomisk	
Skærm diagonal *	60,5 cm (23.8")	VESA montering *	✓
Skærmopløsning *	1920 x 1080 pixel	Panel montering grænseflade	100 x 100 mm
HD-type *	Fuld HD	Skærmvisning (OSD)	✓
Naturligt aspektforhold *	16:9	OSD-sprog	Traditionelt kinesisk, Tysk, Engelsk, Fransk, Japansk, Hollandsk, Polsk, Russisk
Skærmteknologi *	LED	Plug and play	✓
Paneltype *	IPS		
Berøringsskærm *	✓		
Berøringsskærm teknologi	Projekteret kapacitivt systemet		
Berøringsteknologi	Multi-touch		
Antal simultane touchpunkter	10		
Skærmens lysstyrke (spidsbelastning)	600 cd/m ²		
Skærmens lysstyrke (typisk)	600 cd/m ²		
Skærmens lysstyrke	525 cd/m ²		
Responstid *	5 ms		
Målingstype af responstid	GTG (Gray to Gray)		
Skærm form *	Flad		
Billedformat	16:9		
Kontrastforhold (typisk) *	1000:1		
Synsvinkel, horisontal	178°		
Synsvinkel, vertikal	178°		
Vis antal farver *	16.7 millioner farver		
Responstid (hurtig)	5 ms		
Pixel pitch	0,275 x 0,275 mm		
Horizontal scanningsområde	30 - 83 kHz		
Synlig størrelse, horisontal	52,7 cm		
Synlig størrelse, vertikal	29,6 cm		
Skærm diagonal (metrisk)	60,5 cm		
Overfladehårdhed	7H		
Præstation		Strømstyring	
NVIDIA G-SYNC *	✗	Energieffektivitetsklasse (SDR) *	E
AMD FreeSync *	✗	Energieffektivitetsklasse (HDR) *	Ikke tilgængelig
Lav Blue Light teknologi	✓	Energiforbrug (SDR) pr. 1000 timer *	15,4 kWh
		Strømforbrug (typisk) *	22 W
		Strømforbrug (standby) *	1,5 W
		Strømforbrug (slukket)	0,3 W
		Vekselstrømsindgangsspænding	100 - 240 V
		Vekselstrømsindgangsfrekvens	50/60 Hz
		Strømforsyningstype	Intern
		Vægt & størrelser	
		Bredde (med stativ)	561,5 mm
		Dybde (med stativ)	239,5 mm
		Højde (med stativ)	366 mm
		Vægt (med stativ)	8,2 kg
		Facet bredde (side)	1,73 cm
		Facet bredde (øverste)	2,03 cm
		Facet bredde (bund)	2,03 cm
		Emballeringsdata	
		Pakkebredde	650 mm
		Pakkedybde	155 mm
		Pakkehøjde	430 mm
		Pakkevægt	10 kg
		Emballage indhold	
		Kabler inkluderet	Vekselstrøm, USB, HDMI

Multimedie		Emballage indhold	
Antal højttalere	2	Hurtig start guide	✓
Udgangseffekt (RMS)	4 W	Bæredygtighed	
Indbyggede højttaler(e) *	✓	Bæredygtighedscertifikater	ErP
Indbygget kamera *	✗	Andre funktioner	
Design		Kode for international beskyttelse (IP)	IP1X
Produktfarve *	Sort	Kompatible operativsystemer	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Frontkantfarve	Sort		
Glas tykkelse	3,6 mm		
Porte & Grænseflader		Brugerkontrol	Picture adjust (brightness, contrast, i-Style color, adv. contrast, ECO mode, OD, X-Res), color settings (gamma, RGB range, color. temp.), image settings (video mode adjust, blue light reducer, sharp & soft), OSD (H. pos., V. pos., time, background, rotate, language, display information), extra (reset, DDC/CI, signal select, volume, mute, led, opening logo, touch switch)
Indbygget USB-hub *	✓		
USB-hub-version	3.2 Gen 1 (3.1 Gen 1)		
Antal downstream-porte	2	Lysstyrke	525 cd/m ²
Antal USB type-A downstream-porte	2		
USB-berøringsporte	✓		
HDMI *	✓	Aktiv skærmområde (B x H)	527 x 296,5 mm
Antal HDMI-porte	1		
Antal DisplayPorts	1		
Udgang til hovedtelefoner *	✗	Touch method	stylus, finger, glove
HDCP	✓		
		Antal USB-porte	2
		Vægt	8,2 kg
		Højde	366 mm
		Bredde	561,5 mm
		Dybde	239,5 mm
		Kontrolpanel	Menu, Scroll up/ Eco, Scroll down/ Volume, Enter/ Input select, Power
		Compliance-certifikater	CE, cTUVus, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
		Certificering	CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA



4948570122905

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.